



LENNOX®

LENNOX® ECOLEAN (COOLING ONLY)



Suitable for small office buildings, residential buildings, hotels and hospitals; Lennox® Ecolean Chillers utilise R410A multi scroll compressors, Owllet™ variable speed fans and variable water flow which optimise performance, reduce noise and minimise carbon footprint.

Key features

- 7 day programming via the Climatic™ control which manages power consumption according to use.
- Plug and play integrated hydraulic module.
- Small footprint allows for compact indoor or outdoor installation.
- Best in class acoustic performance producing -7 dB(A) average noise level reduction compared to traditional units.
- eDrive delivers cost savings of up to 75% on pump energy consumption.

Part Number	Capacity (kW)		Power Supply	Dimensions	Weight	Connections	Refrigerant		
	Cooling	Heating	(V / Ph)	(mm)	(kg)	(mm)	Type	Circuits	Charge (kg)
EAC472SM4HY	44.1	-	380-415 / 3	1635x1960x1195	480.0	50.80	R410A	1	11.00
EAC552SM4HY	50.7	-	380-415 / 3	1635x1960x1195	492.0	50.80	R410A	1	12.20
EAC672SM4HY	63.4	-	380-415 / 3	1635x1960x1195	534.0	50.80	R410A	1	15.50
EAC812SM4HY	75.4	-	380-415 / 3	1635x1960x1195	578.0	50.80	R410A	1	19.50
EAC1003SM4HY	88.2	-	380-415 / 3	2155x2250x1420	663.0	63.50	R410A	2	23.50
EAC1103SM4HY	102.0	-	380-415 / 3	2155x2250x1420	831.0	63.50	R410A	2	26.00
EAC1203SM4HY	112.0	-	380-415 / 3	2155x2250x1420	964.0	63.50	R410A	2	27.00
EAC1303SM4HY	126.0	-	380-415 / 3	2155x2250x1420	1,016.0	63.50	R410A	2	30.00
EAC1403SM4HY	139.0	-	380-415 / 3	2155x2250x1420	1,045.0	63.50	R410A	2	33.70
EAC1604SM4HY	149.0	-	380-415 / 3	2250x2250x2300	1,347.0	76.20	R410A	2	36.20
EAC1804SM4HY	174.0	-	380-415 / 3	2250x2250x2300	1,703.0	76.20	R410A	2	45.00
EAC2104SM4HY	199.0	-	380-415 / 3	2250x2250x2300	1,723.0	76.20	R410A	2	47.00