

LENNOX® NEOSYS (COOLING ONLY)

Suitable for medium and large office buildings, hotels, hospitals and industrial applications; Lennox® Neosys Chillers offer excellent architectural integration, easy installation and maintenance, as well as high performance energy saving.

Key features

- State of the art design for perfect architectural integration.
- Flat top, very low unit height (< 2m) for discrete installation.
- Aesthetic side anti-intrusion grilles as standard.
- Hydraulic module mounted in a soundproofed technical cabinet.
- Compact hydraulic equipment with pump providing 150 or 250 kPa external static pressure.
- Active Acoustic Attenuation System, adjustable sound level during day and night to satisfy local environmental constraints.
- eDrive, variable speed pump, electronically adjusted water flow rate.

Part Number	Capacity (kW)		Power Supply	Dimensions	Weight	Connections	Refrigerant		
	Cooling	Heating	(V / Ph)	(mm)	(kg)	(mm)	Type	Circuits	Charge (kg)
NAC200DNM6M	208.2	-	400 / 3	2025x2280x3590	1,983.0	101.60	R410A	2	12.40
NAC230DNM6M	235.7	-	400 / 3	2025x2280x3590	2,011.0	101.60	R410A	2	12.30
NAC270DNM6M	272.8	-	400 / 3	2025x2280x3590	2,278.0	101.60	R410A	2	14.10
NAC300DNM6M	307.6	-	400 / 3	2025x2280x4620	2,676.0	101.60	R410A	2	18.20

